



Combine harvesters

DOMINATOR 40

TERRA TRAC

CLAAS

DOMINATOR 40 TERRA TRAC.

Robust cutterbar.

The cutterbar allows you to make full use of the potential of the DOMINATOR 40. The twin knife drive and the reel ensure an even crop flow. Hardened edges on the intake auger, a slip clutch mechanism – every detail has been developed for challenging conditions.

Proven straw-walker technology.

The four straw walkers work in perfect harmony with the threshing mechanism. Residual grain separation takes place over a length of 3300 mm. Large volumes of straw are transported rapidly and loosely. Proven CLAAS technology for impressive grain and straw quality.

Single-lever control.

Comfort and practicality rolled into one: a single lever for controlling both movement and function of the machine ensures fatigue-free operation. The ergonomic control panel with its display layout provides all relevant machine information.

Powerful engine.

The 76 hp TATA engine impresses with its fuel efficiency, high reliability and extended service life. With its high torque, the engine is able to overcome even the most demanding harvest conditions. Maximum power. Maximum benefit.

FIRST CLAAS SERVICE.

You can count on the professional and reliable support of the FIRST CLAAS SERVICE team at every stage. CLAAS importers and dealers provide fast spare parts supply and reliable customer service worldwide.





- 1 High-quality carbon-fibre roof
- 2 Single lever for movement and function control
- 3 Ergonomic and intelligent control panel
- 4 Robust cutterbar with width of 2415 mm (7.92 ft.)
- 5 Classic CLAAS threshing mechanism with diameter of 600 mm and width of 800 mm
- 6 Straw walker technology for clean separation
- 7 Fully enclosed grain tank with a grain capacity of 1700 l
- 8 Fast and tidy unloading system with safety lock
- 9 TATA engine with 76 hp (BS III exhaust standard)
- 10 CLAAS rubber track roller unit for very wet field conditions



Proven straw-walker technology



Single-lever control



Powerful engine



FIRST CLAAS SERVICE

DOMINATOR		40 TERRA TRAC
Cutterbar		
Effective cutting width	mm (ft.)	2415 (7.92)
Threshing system		
Drum diameter	mm	600
Drum width	mm	850
Drum speed	rpm	600
Residual grain separation		
Straw walkers	No.	4
Straw walker width	mm	196
Straw walker length	mm	3300
Separation area	m ²	2.5
Crop cleaning		
Upper sieve	mm	793 x 1443
Lower sieve	mm	793 x 1443
Total sieve area	m ²	2.34
Fan speed	rpm	1200-1500
Grain tank		
Capacity	l	1700, closed
Offloading rate	l/s	27
Engine		
Manufacturer		TATA
BS III emissions standard		
Model		497 TC
Cylinders / displacement	No. / cc	4 / 3783
Maximum output	hp	69
Engine speed	rpm	2200
Fuel tank capacity	l	100
Dimensions		
Length (with front attachment)	mm	7185
Length (without front attachment)	mm	5410
Height	mm	3094
Width	mm	2832
Travel width	mm	2015
Width	mm	1850
Weights		
Machine weight	kg	5000
Front attachment weight	kg	600



As CLAAS continuously develops its products to meet customers' requirements, all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specification.