

MARKANT BALER 650

- Pick-up width: 1.86 m
- Slip clutch and shear bolt to protect baler
- Two strengthened dual crank feeders
- High baling density with heavy, robust rams and bale chamber
- Shaft drive for feeders, knotters and needle, with capacity for ten reels
- Reliable all twine knotter

Versatile and rugged



| Tyres | |
|-------|--------------------|
| Left | 11.5/80-15.3 10 PR |
| Right | 10.0/80-12 10 PR |

| mm | 5550 |
|----|----------|
| mm | 6380 |
| mm | 2930 |
| mm | 1800 |
| kg | 1800 |
| | mm mm |


| Hydraulic Pick-up | Standard |
|-------------------|----------|
| Pivoted drawbar | Optional |

CLAAS continually develops its products to meet customer's requirements, so all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications.



High compaction

- The new bale chamber shape enables the MARKANT to produce heavier bales
- More kilos per bale mean more tonnes per truck, for lower transport costs



Strengthened pick-up

- New: strengthened pick-up, for working in any conditions
- Controlled pick-up for longer service life



Pivoted drawbar

- Lesser turning radius
- Attached to lower link, so drawbar can be lifted / lowered when crossing bunds



Twine box

- New twine box with capacity for ten reels
- Better access to the ten reels

CLAAS Agricultural Machinery Private Limited 487/B1,14th Cross, 4th Phase Peenya Industrial Area, Bangalore – 560058, Karnataka Tel: +91-80-67167000

E-mail: marketing.india@claas.com www.claas.co.in







Feb/201